

Full Duplex Digital Intercom System



DW-10C

Dual Channel Base Station

Included: Multi-port charger, Batteries



DW-10H

Lightweight Headset



DW-10T

Lightweight Beltpack

Outstanding Range

Full duplex communication up to 400 yards in any direction from Base Station.

Dual Channel with Conferencing

Two groups of four users communicate separately or all together in conference mode.

Digital, Full Duplex Voice

Dect frequency band 1900MHz) is reserved by FCC for "PCS" voice communication only.

Expandable

Stat small, and field programmable headsets. Up to 8 total.

Totally Portable

Ac wall plug, rechargeable batteries (6 hrs), and AA disposable battery sled included.

Simple / Instant Setup

Self tuning, no antenna required.

No FCC License Required

USA, Canada, Europe & Australia certified.

Standard	DECT6.0 (Digital Enhanced Cordless Telecommunications)
Frequency	1920—1930GHz (USA), 1880—1900GHz (EURO)
Channel bandwidth	1.728MHz
Modulation type	GFSK
Transmission speed	1.152 Mbps (Baud rate)
Duplexing	Time division duplex (TDD)
Speech encoding	ADPCM / 32kbit/s
RF accessing	Time division multiple access (TDMA)
Range	400m in open space
Base power supply	AC adaptor/ INPUT 110-240Vac, OUTPUT 9.0Vdc 1000mA
Headset power supply	Rechargeable battery: 3.7V/1000mAh
Charge time	Initially 6 hours
Operation time	100 hours in standby, 10 hours in talk
Normal condition of use	0°C to 40°C
Storage temperature	-10°C to 60°C

AZDEN corporation

200 Valley Road, Suite 101, Mt. Arlington, NJ 07856, Phone (973)810-3070, Fax (973)810-3076

e-mail: sales@azdencorp.com, web site: www.azdencorp.com